

HDMI 4K Extender With Loop Out, Audio Extraction, Dual POC Model : KVE807K6

FEATURES

- HDMI2.0 Extender, Bandwidth 18Gbps, HDR10, Power over Cable (PoC) allows one power adapter to power both the TX & RX units
- Transmit up to 70m under 4K@60Hz YUV4:4:4, 90m under 4K@30Hz/1080P over single Cat5e/6 cable
- 1x HDMI loop out on transmitter
- Support EDID management
- Support wide band IR Pass through
- HDMI audio sampling rate up to 192KHz, max LPCM 7.1 channel
- Support S/PDIF and PCM2.0 analog audio extraction
Support 3.5mm and Toslink Audio Out
- Support Dolby True HD, PCM and DTS-HD master audio
- Support Micro USB port to upgrade new firmware



PACKAGE CONTENTS

- 1 x HDMI Transmitter + 1 x HDMI Receiver
- 1 x IR TX Emitter, 1 x IR RX Receiver
- 1 x 12V DC Adapter
- 1 x User Manual - 4 x Mounting Ears

SPECIFICATION

Operating Temperature	-5° to 40°C
Operating Humidity	5 to 90%RH (No Condensation)
Connectors on Transmitter	HDMI Receptacle x2, IR Receptacle x1, 1xHDMI input Power DC Receptacle x1, 1xHDMI loop output
Connectors on Receiver	HDMI Receptacle x1, IR Receptacle x1
Resolution outputs	4k@60hzYUV4:4:4/ 4k@30HZ/1080p
Output Video Signal	HDMI

Audio format supported	DTS-HD Master Audio, Dolby True HD, LPCM7.1, PCM etc.
Transmission Distance	up to 70m under 4K@60Hz YUV4:4:4 90m under 4K@30Hz/1080P
Dimension (L×W×H)	TX & RX: L75.8mm×W72.2mm × H18mm;
Power supply	DC 12V1A Power supply
Power consumption	3.8W(MAX)
Net Weight	TX: 305g; RX: 305g

CONNECTION DIAGRAM

